


# Technical datasheet



## 28 HSA-LCH

Tested according the European norm 12825

### General characteristics

|              |   |  |
|--------------|---|--|
| Measurements | : | 600 x 600 mm   |
| Weight       | : | +/- 9,5 kgs  |
| Core         | : | 28 mm chipboard - density 720 kgs/m <sup>3</sup> -E1 |
| Bottom side  | : | Galvanised steel 0,5mm                               |
| Upper side   | : | Aluminiumfoil 0,05 mm                                |
| Edge banding | : | Conductible PVC 0,6 mm                               |

### System characteristics

|  |   |                            |
|--|---|----------------------------|
| Class of element                                       | : | 1                          |
| Ultimate load  | : | ≥ 4 kN                     |
| Safety factor  | : | 2                          |
| Point load<br>(= ultimate load/safety factor)          | : | 2 kN                       |
| Class of deflection<br>(max 2,5mm deflection by 2Kn)   | : | A                          |
| Divided load per m <sup>2</sup><br>(Theoretical value) | : | 10kN–15kN / m <sup>2</sup> |

### Fire characteristics

|                 |   |                               |
|-----------------|---|-------------------------------|
| Fire resistance | : | F30 according DIN 4102-2      |
| Fire reaction   | : | Class B1 according DIN 4102-1 |

### Electrical resistance

<10<sup>7</sup> -Ω

#### Jansen Products NV

Fabriekstraat 4  
3670 Meeuwen  
BELGIUM

Tel : +32 11 79 33 00  
Fax: +32 11 79 33 01  
info@jansenproducts.be  
www.groupjansen.com

complete certificates on request